

Product Information Sheet

WIPE OFFTM

GP PLUS REMOVER

Graffiti Remover for Brickwork etc.

Description:

- ✓ Removes Marker & Felt Tip Pens, Aerosol Paints, Correction Fluids, Nail Varnish etc.
- ✓ Low hazard Product, requires only plastic gloves and safety glasses.
- ✓ Contains products which are derived from natural, renewable resources.
- ✓ Supplied as a gel to prevent running on vertical surfaces,
- ✓ Quick acting – removes alkyd paints off aluminium in under 1.5 minutes.
- ✓ Biodegradable and environmentally friendly.

Not suitable for some plastics or prepainted surfaces. Use Polycarbonate Cleaner instead.

Properties:

Specific Gravity	1.002 gram/ml @ 20 ⁰ C
Viscosity:	1500 cSt.
Colour:	Straw
Number of coats:	One to Two
Appearance:	Thickened liquid
Cleaner:	Water
Solubility in water:	> 90%
Vapour pressure:	0.1 mm Hg @ 200 C.
Coverage rate:	6-8 sq. metres per litre depending upon porosity & heaviness of graffiti deposits.

Application Methods:

Apply generously onto the areas to be treated with a brush. Allow to soften the graffiti deposits for up to 5 minutes. Work the Remover into the graffiti with a scrubbing action until all the graffiti is removed. Wipe off the remover & paint with an absorbent paper towel etc.. Clean the surface down with water to remove any last traces of Remover and / or graffiti. Stubborn

Aqualine (Coatings) Limited

deposits may need a second treatment.

Do not use when it is raining as being water soluble the Remover will be less effective and in heavy rain will be washed away before it has had time to act on the graffiti.

Do not use on thermoplastics or prepainted surfaces as the powerful constituents will attack and soften these materials.

Cleaning:

Clean spillages and equipment with clean water or warm soapy water followed by a clean water rinse.

Storage:

Store in covered, ventilated areas out of direct sunlight between 0°C and 29°C.

Not classified as flammable under the current regulations however being organic the material will burn in a fire.

Shelf life: minimum 12 months in unopened, correctly stored original containers.

Safety Data:

Read the Material Safety Data Sheet before use.
We recommend the use of plastic gloves, safety glasses and suitable protective clothing. As the remover will dissolve unknown paints we recommend operatives avoid skin contact to prevent absorption of unknown materials in solution.

Date: October 1999

Revision: 1

Ref.: GPP152/DISK01

Aqualine (Coatings) Limited, Unit 33, Business & Innovation Centre, Sunderland Enterprise Park East, Wearfield, Sunderland. SR5 2TA.

Tel: +44 (0) 191 516 6232. Fax: +44 (0) 191 516 6005. Email: info@aqualine-coatings.co.uk

Website: <http://www.aqualine-coatings.co.uk>