

Product Information Sheet

TM

WIPE OFF

AQUALINE Polycarbonate Cleaner 2

TECHNICAL DATA

DESCRIPTION: A unique blend of environmentally friendly solvents which combine high removal power with low hazard. Specially designed for the cleaning of Polycarbonate Sheet and similar plastics such as is used on Signage and modern Bus Shelters the material will remove Felt tip, marker pen, crayon, and Aerosol paints without attacking the Polycarbonate surface. Supplied as a gel the material is also suitable for use as a general purpose Remover on pre-painted surfaces such as street furniture. This modified version cleans off a wider range of graffiti products including Correction Fluids.

PROPERTIES:	Specific Gravity	1.03 - 1.04
	Viscosity	>40 sec. [ISO 4 mm Cup] @ 20° C
	Colour	Clear, semi gelled liquid
	Drying times	Not applicable
	Wet film Thickness	75 microns
	Dry Film Thickness	Not applicable
	Number of Coats	One to Two
	Cleaner:	Water
	Coverage Rate:	6 - 8 Square metres per
		litre (depending on the surface roughness etc.)

APPLICATION METHODS:

Aqualine (Coatings) Limited

Brush or roller Aqualine Polycarbonate Cleaner onto the area to be treated at the recommended coverage rate. Leave for up to 5 minutes. Remove graffiti by rubbing the surface with a brush or foam pad, using more of the Remover, until all the graffiti has been removed. Wash the treated surface with a minimum of two applications of clean water.

Do not apply Remover if frosty or when temperatures are below 5° C

Apply to surfaces between 5 and 29° C.

CLEANING

Clean spillage's and equipment with clean water or warm, soapy water followed by a clean water rinse.

STORAGE

Store in covered, ventilated areas which are between 1° C and 25°C.
Keep out of direct sunlight.

Flash Point - greater than 55° C [Abel closed cup - 68° C]

Shelf life 12 months minimum in unopened, correctly Stored containers.

SAFETY DATA

Health and Safety Data is shown on each container and on the Material Safety Data Sheet.

Date: 02/8/98
Revision: 1
Ref.: PC01/D04

Aqualine (Coatings) Limited, Unit 33, Business & Innovation Centre, Sunderland Enterprise Park East, Wearfield, Sunderland. SR5 2TA.

**Tel: +44 (0) 191 516 6232. Fax: +44 (0) 191 516 6005. Email: info@aqualine-coatings.co.uk
Website: <http://www.aqualine-coatings.co.uk>**