

Product Information Sheet

WIPE OFFTM

WAX GRAFFITI SEALER

Water Based wax Graffiti Sealer for Brickwork, prepainted surfaces etc..

Description: A water based blend of special waxes formulated to provide a tough, waterproof, clear film. It is virtually undetectable once applied and can be applied to stone, concrete, wood, and prepainted surfaces. A thin barrier coating is formed which is simply removed by application of a hot water / steam lance which melts the wax and any graffiti. This sacrificial sealer then comes cleanly off taking the graffiti with it. Once cleaned the area is easily re-protected by applying more Wax Sealer to the cleaned areas.

Properties:

Specific Gravity	1.05 gram/ml @ 20° C
Viscosity:	< 50 sec. [ISO 4 mm Cup] @ 20° C..
Colour:	Milky mobile liquid.
Number of coats:	One to Two
Cleaner:	Water
Drying Times:	Touch - 15 min. @ 20° C. Hard - 60 min. @20° C.
Wet Film Thickness:	80 - 100 microns.
Dry Film Thickness:	20 - 25 microns
Coverage rate:	6 -10 sq. metres per litre depending upon porosity & surface profile of the substrate

SURFACE PREPARATION

Remove Loose paintwork, unsound substrate, dirt, grease, oil etc.. Ensure the surface is dry, or slightly damp, but **not wet** .

Application Methods:

Unpainted Surfaces.

Brush or roller Aqualine Wax Sealer onto the surface to be treated at the recommended coverage rate. **Do not apply too thickly** as this can create a white “bloom” making removal more difficult.

Do not apply sealer while raining or if rain is imminent.

Do not apply sealer if frost is likely within the drying time.

On rough surfaces apply sparingly with a brush. This stops the sealer collecting in the “valleys” of the surface and creating runs.

Painted Surfaces

Brush, roller or spray onto the surface to be treated. Apply at the recommended coverage rate observing the same rules as for unpainted surfaces.

Removal:

To remove hot water at 80° C + is required. The most efficient method is to use a hot water/ steam lance played over the surface. The melted wax is flushed off the substrate and brings off all graffiti with it.

Cleaning:

Clean spillages and equipment with clean water or warm soapy water followed by a clean water rinse before the coating dries out. If the sealer has been allowed to hard onto equipment then it should be soaked in graffiti remover overnight, then washed in warm soapy water and rinsed in clean, warm water.

Storage:

Store in covered, ventilated areas out of direct sunlight between 1°C and 25°C.

Not classified as flammable under the current regulations.

Shelf life: minimum 6 months in unopened, correctly stored original containers.

Safety Data:

Read the Material Safety Data Sheet before use.

We recommend the use of plastic gloves, safety glasses and suitable protective clothing.

Date: February 1999

Rev.: 1.1

Ref.: WGS17/ CDR01

**Aqualine (Coatings) Limited, Unit 33, Business & Innovation Centre, Sunderland Enterprise Park East,
Wearfield, Sunderland. SR5 2TA.**

Tel: +44 (0) 191 516 6232. Fax: +44 (0) 191 516 6005. Email: info@aqualine-coatings.co.uk

Website: <http://www.aqualine-coatings.co.uk>